

# **Galvanized Chain Link**



### Galvanized Chain-Link... made to be versatile

Permafused, the next generation in color chain link fence systems, offers unparalleled performance over ordinary systems, featuring a fused and adhered coating that offers superior protection. Its outstanding resistance to ultra violet light and corrosive environments prevents premature fading and decay. It is an ideal choice for commercial applications that need the security of a chain link fence system and an appearance that blends in beautifully with the environment.

Highway

#### Galvanized Fencing System

All steel components are hot-dip zinc coated and guaranteed for 12 years.



Security

12 Year Warranty



Meets and Exceeds all ASTM Standards

#### Galvanized After Weaving (GAW)

This process forms or weaves chain-link into a fabric first, and then soaks it in a large galvanized bath which adheres the zinc coating. This ensures that all the wire is coated, even the cut ends created during the weaving process.



Commercial

#### Galvanized Before Weaving (GBW)

In this process, the wire is pre-galvanized before it is formed into a fabric. The weaving process creates an exposed cut end that will lack coating and be more apt to some minor rust in wet and severe weather conditions.





## **Galvanized Chain Link Recommendations**

	Reside	ential	Commercial			
Fabric Type	Galvanized After Weaving and Galvanized Before Weaving		g Galvanized After Weav	Galvanized After Weaving		
Fabric Gauge	9, 11, 11.5, and 12.5 gauge		6, 9, and 11 gauge	6, 9, and 11 gauge		
Fabric Mesh	1-1/4", 2", 2-1/4", 2-1/2", and 2-3/8"		3/8", 1/2", 5/8", 1", 1-1,	3/8", 1/2", 5/8", 1", 1-1/4", 1-1/2", 1-3/4", and 2"		
Fabric Height	3', 42", 4', 5', and 6'		3', 42", 4', 5', 6', 7', 8', 9',	3', 42", 4', 5', 6', 7', 8', 9', 10', and 12'		
Fabric Selvage	Knuckle - Knuckle (KK) for 5' and Under. Knuckle - Knuckle (KK) or Knuckle - Twist (KT) for 6'.			Knuckle - Knuckle (KK) for 5' and Under. Knuckle - Knuckle (KK) or Knuckle - Twist (KT) for 6' and over.		
	1			X		
Top Rail			Top Rail			
3' to 5' High	1-3/8" O.D. 17 Gauge 1-3/8" O.D. 16 Gauge			1-5/8" O.D. Deluxe Quality (DQ) 1-5/8" O.D. Full Weight Pipe		
6' High and over	1-3/8" O.D. 17 Gauge 1-3/8" O.D. 16 Gauge 1-5/8" O.D. 16 Gauge			1-5/8" O.D. Deluxe Quality (DQ) 1-5/8" O.D. Full Weight Pipe		
Line Posts			Line Posts	Line Posts		
3' to 5' High	1-5/8" O.D. 16 Gauge		1-7/8" O.D. Full Weigh 2-3/8" O.D. Commercia 2-3/8" O.D. Deluxe Qua	1-7/8" O.D. Deluxe Quality (DQ) 1-7/8" O.D. Full Weight Pipe 2-3/8" O.D. Commercial Quality (CQ) 2-3/8" O.D. Deluxe Quality (DQ) 2-3/8" O.D. Full Weight Pipe		
6' High and over	1-7/8" 0.D. 16 Gauge		2-3/8" 0.D. Deluxe Qua	2-3/8" O.D. Commercial Quality (CQ) 2-3/8" O.D. Deluxe Quality (DQ) 2-3/8" O.D. Full Weight Pipe		
Terminal Posts	1.0		Terminal Posts			
3' to 5' High	1-7/8" O.D. 16 Gauge 2-3/8" O.D. 16 Gauge 2-3/8" O.D. 16 Gauge		3' to 5' High	2-3/8" 0.D. Commercial Quality (CQ) 2-3/8" 0.D. Deluxe Quality (DQ) 2-3/8" 0.D. Full Weight Pipe 4" 0.D. Commercial Quality (CQ) 4" 0.D. Deluxe Quality (DQ) 4" 0.D. Full Weight Pipe		
6' High and over						
			For Heavy Gates	6-5/8" O.D. Full Weight Pipe 8-5/8" O.D. Full Weight Pipe		
Gates						
abric Same Gauge and Mesh as Chain Link Selected						
Frame Same as Top Rail Se		Same as Top Rail Selected				
Fittings						
		Hot-Dipped Galvanized Pressed Steel	ed Galvanized Pressed Steel			
Caps, Eye Tops, Rail Ends		Malleable, Cast Iron Steel, Pressed Steel, or Die Cast Aluminum				
Tie Wires		Aluminum or Galvanized Steel				
Slats - Privacy						
Material Composition Polyethylene Thermoplastic						
· · ·						

#### MasterHalco.com | 888-MH-Fence

Branch service centers are located throughout North America.



Available from: